



Alloy Bolt Type Anchor Shackles



Load Rated®



- Working Load Limit is permanently shown on every shackle.
- Alloy bows, alloy bolts.
- Quenched and Tempered.
- Forged Alloy Steel 30 thru 175 metric tons. Cast Alloy Steel 200 thru 400 metric tons.
- Pins are galvanized and painted red.
- All sizes are individually proof tested to 2.0 times the working load limit.
- Meet or exceed all of the requirements of ASME B30.26.
- Sizes 4 3/4, 5, and 6 are style G2140-E with alloy Easy-Loc® bolt.

G-2140 / S-2140

G-2140E

Meet the requirements of Federal Specification RR-C-271D
 Type IVA, Grade Bm Class 3

G-2140E / S-2140E Crosby® Alloy **Crosby Easy-Loc®** Shackles

Nominal Shackle Size (in.)	Working Load Limit (T)	Stock No.		Weight Each (lbs.)	Dimensions (in.)													Tolerance +/-	
		G-2140E	S-2140E		A	B	C	D +/- .02	E	F	G	H	J	K	L	M	A	E	
4-3/4	† 200	1021422	—	452	7.25	10.50	5.00	4.75	15.19	4.58	20.84	23.11	27.81	11.00	4.75	1.75	0.25	0.25	
5**	† 250	1021442	—	594	8.50	12.00	5.63	5.00	18.50	4.48	23.63	24.28	32.63	13.00	5.00	1.75	0.25	0.25	
6**	† 300	1021460	—	791	8.38	13.00	6.06	6.00	18.72	4.89	24.76	25.45	34.28	13.00	5.88	1.75	0.25	0.25	

G-2140 / S-2140 Crosby® Alloy Bolt Type Shackles

Nominal Shackle Size (in.)	Working Load Limit (t)*	Stock No.		Weight Each (lbs.)	Dimensions (in.)													Tolerance + / -	
		G-2140	S-2140		A	B	C	D +/- .02	E	F	G	H	J	K	L	A	E		
1-1/2	30	1021110	1021129	18.8	2.38	3.62	1.62	1.63	5.75	1.39	6.88	7.73	10.00	3.88	1.53	0.13	0.25		
1-3/4	40	1021138	1021147	33.8	2.88	4.19	2.25	2.00	7.00	1.75	8.81	9.33	12.34	5.00	1.84	0.13	0.25		
2	55	1021156	1021165	49.9	3.25	4.81	2.40	2.25	7.75	2.00	10.16	10.41	13.68	5.75	2.08	0.13	0.25		
2-1/2	85	1021174	1021183	103	4.12	5.81	3.12	2.75	10.50	2.62	12.75	13.58	17.90	7.25	2.71	0.25	0.25		
3	120	1021192	-	162	5.00	6.50	3.63	3.25	13.00	3.00	14.62	15.13	21.50	7.88	3.12	0.25	0.25		
3-1/2	† 150	1021218	-	268	5.25	8.00	4.38	3.75	14.63	3.75	17.02	17.62	24.88	9.00	3.62	0.25	0.25		
4	† 175	1021236	-	332	5.50	9.00	4.56	4.25	14.50	4.00	18.00	20.37	25.68	10.00	4.00	0.25	0.25		
7**	† 400	1021478	-	1200	8.25	14.00	7.25	7.00	22.50	6.50	26.00	28.68	40.25	13.00	6.00	0.25	0.25		

* NOTE: Maximum Proof Load is 2.0 times the Working Load Limit. Minimum Ultimate Load is 4 times the Working Load Limit on 200 thru 400 metric tons.
 For sizes 30 thru 175 metric tons, Minimum Ultimate Load is 5.4 times the Working Load Limit.

** Cast Alloy Steel.

† Furnished with Round Head Bolts with an eyebolt for handling.