
Trench Cover Hoist Rings





- Designed to simplify the lifting and placement of steel plates used to cover trenches in streets.
- Provides a standard fitting to be used in place of products not designed for trench cover applications.
- Capacities of 5,000, 10,000 & 15,000 lbs. for plate thicknesses of 3/4" to 1-1/2".
- · Detailed welding instructions included with every hoist ring.
- Forged bail provides the following:
 - Easily readable raised lettering showing the name Crosby or "CG" and PIC code for material traceability.
 - More durability provides the increased "Toughness" desired in potentially abusive field conditions
- 180 degree pivot and 360 degree rotation at full capacity.
- Design Factor of 5 to 1.
- Individually Proof Tested to 2-1/2 times Working Load Limit.
- All sizes are RFID EQUIPPED.





HR-500 Trench Cover Hoist Rings Coil Threads

•

			Dimensions (in)								
HR-500 Stock No.	Working Load Limit (Ib)*	Weight Each (Ib)	Coil Thread Size A	Effective Thread Projection Length B	с	D	Radius E	F	G	н	J
1017907	5000	5.6	1" - 3.5	1.00	5.90	5.50	1.25	.75	4.20	2.50	.77
1017916	10000	15.7	1-1/4" - 3.5	1.00	8.27	7.00	1.63	1.00	6.25	3.25	.81
1017925	15000	29.8	1-1/2" - 3.5	1.50	10.63	9.13	2.00	1.25	7.82	4.00	.80

*Ultimate Load is 5 times the Working Load Limit.

-500
UIA TYPEAL CLEARAN ALL AROUND

HRN-500 Trench Cover Nuts -

					Dimensions (in)		
	HRN-500 Stock No.	Working Load Limit (Ib)	Weight Each (lb)	Coil Thread Size	Nut Diam. K	TrenchCover Hole Diam. L	Nut Thickness M
	1063405	5000	1.2	1" - 3.5	3.00	3.12	.75
	1063414	5000	1.4	1" - 3.5	3.00	3.12	.88
	1063423	5000	1.6	1" - 3.5	3.00	3.12	1.00
	1063432	10000	1.1	1-1/4"- 3.5	3.00	3.12	.75
VCE	1063441	10000	1.3	1-1/4"- 3.5	3.00	3.12	.88
90-E	1063450	10000	1.5	1-1/4"- 3.5	3.00	3.12	1.00
	1063454	10000	1.9	1-1/4"- 3.5	3.00	3.12	1.25
	1063458	10000	2.3	1-1/4"- 3.5	3.00	3.12	1.50
	1063469	15000	2.0	1-1/2"- 3.5	3.50	3.62	1.00
	1063478	15000	2.6	1-1/2"- 3.5	3.50	3.62	1.25
	1063487	15000	3.1	1-1/2"- 3.5	3.50	3.62	1.50

Trench Cover Lifting Ring Tools and Accessories



HR-500HG Hole Gauge Aids in determining when studs and

plate nuts need replacing.

Coil Thread Size (in)	HR-500HG Stock No.	Weight Each (lb)	
1.00 - 3.5	1064666	.6	
1.25 - 3.5	1064675	.8	
1.50 - 3.5	1064684	1.0	



HR-500TC Thread Clean-Up Tool

Cleans dirt and other material as from nut threads.

Coil Thread Size (in)	HR-500TC Stock No.	Weight Each (Ib)
1.00 - 3.5	1064639	1.2
1.25 - 3.5	1064648	1.7
1.50 - 3.5	1064657	1.9



HR-500WF Weld Fixture

Holds nut securely in place to ease in initial tack welding.

	Coil Thread Size (in)	HR-500WF Stock No.	Weight Each (Ib)
]	1.00 - 3.5	1064602	1.8
	1.25 - 3.5	1064611	2.1
]	1.50 - 3.5	1064620	2.5

Copyright © 2019 The Crosby Group LLC All Rights Reserved